panconnect•

BASICS

CARIQ

CARIQ is available in five different sizes and various configurations, including sockets, USB charging, connectors, and an innovative integrated grommet. It provides a distinctive solution for consolidating all cables into one component, suitable for desks, as well as meeting room setups. Constructed from dural aluminium and steel, CARIQ prioritizes a minimalist design aesthetic. Its key highlights include competitive pricing, a diverse range of configurations readily accessible from the manufacturer and effortless installation.

High variability with minimalist design

Unique integrated cable grommet

Available with USB-A QC & USB-C 60W PD

Minimum possible panel footprint on the desk

Full metal body with durable coating

Supports wide range of socket standards

| FRENCH type E | SCHUKO type F | UNI VERSAL | ITALY type L | DENMARK type K | SWISS type J | GB type G | US type B |

CARIQ

panconnect•

CARIQ XS

CARIQ XS with sockets only or in combination of socket and USB-C/A charging or grommet

Dimensions (mm)	Weight (g)	Product package (mm / kg)
136,5 × 74 × 62	720	220 × 200 × 100 / 1

Number of sockets	USB-C/A 60W charging	Power cables
1 - 2	0- 1	2.9m, ending with a plug 25cm WIELAND or WINSTA mini

Connector field	Multicable grommet	CUT-OUT
0 - 1	yes, up to 6 cables	130,5 × 68, rounded

CARIQ S

CARIQ S with sockets only, or in combination of sockets, connector field, grommet and USB-C/A charging

Dimensions (mm)	Weight (g)	Product package (mm / kg)
188 × 74 × 62	860	220 × 200 × 100 / 1,2

Number of sockets	USB-C/A 60W charging	Power cables
1 - 3	0 - 1	2.9m, ending with a plug 25cm WIELAND or WINSTA mini

| Connector field	Multicable grommet	CUT-OUT
0 - 1	yes, up to 6 cables	182 × 68, rounded

CARIQ M

CARIQ M with sockets only, or in combination of sockets, connector field, grommet and USB-C/A charging

Dimensions (mm)	Weight (g)	Product package (mm / kg)
239,5 × 74 × 62	1020	360 × 200 × 100 / 1,4

Number of sockets	USB-C/A 60W charging	Power cables
1 - 4	0 - 1	2.9m, ending with a plug 25cm WIELAND or WINSTA mini

Connector field	Multicable grommet	CUT-OUT
0 - 1	yes, up to 6 cables	233,5 × 68, zaoblený

CARIQ L

CARIQ L with sockets only, or in combination of sockets, connector field, grommet and USB-C/A charging

Dimensions (mm)	Weight (g)	Product package (mm / kg)
291 × 74 × 62	1200	360 × 200 × 100 / 1,4

Number of sockets	USB-C/A 60W charging	Power cables
2 - 5	0 - 2	2.9m, ending with a plug 25cm WIELAND or WINSTA mini

Connector field	Multicable grommet	CUT-OUT
0 - 1	yes, up to 6 cables	285 × 68, rounded

CARIQ XL

CARIQ XL with sockets only, or in combination of sockets, connector field, grommet and USB-C/A charging

Dimensions (mm)	Weight (g)	Product package (mm / kg)
342,5 × 74 × 62	1380	400 × 200 × 100 / 1,6

Number of sockets	USB-C/A 60W charging	Power cables
3 - 6	0 - 1	2.9m, ending with a plug 25cm WIELAND or WINSTA mini

Connector field	Multicable grommet	CUT-OUT
0 - 1	yes, up to 6 cables	336,5 × 68, rounded

CARIQ

panconnect•

COLOURS

CARIQ is always offered as all-painted panel including bottom cover and a mounting frame.

WHITE
white coating, finely textured surface, fitting RAL 9003

BLACK
black coating, resistant smooth matt surface, fitting RAL 9005

SILVER
silver metallic, resistant matt surface, fitting RAL 9006

TECHNICAL DETAILS

Main attributes for all sizes of panel CARIQ

USB-C CHARGING SPECIFICATION
PowerDelivery protocol up to 60W

USB-A CHARGING SPECIFICATIONS
QuickCharge 3.0 (up to 5A)

SOCKET
230V/10A (EU), 110V/10A (US)

POWER SUPPLY
110 - 250V, 10A

MATERIALS
dural, stainless steel, steel, ABS plastics (sockets)

INGRESS PROTECTION
IP22

AVAILABLE IN THIS VERSION FROM
2022

POWER CABLES

Panels are always supplied with integrated power cables.

Cable with standard plug type
2.9 meter long cable (not available for US standard)

WINSTA mini
25 cm long pigtail cable with connector (male, 2+PE, 10A)

WIELAND GST18i3
25 cm long pigtail cable with connector (male, 2+PE, 10A)

MULTICABLE GROMMET

All variants can contain multicable grommet for passing the cables through the desk (usually monitor or control display cable)

Magnetic insert with space for single cables

Size of the grommet is 40x 40 mm, it is equipped with hidden magnets for easy manipulation with insert after passing the cables through (from the upper side)

Grommet's insert is painted in the colour of the panel. 3mm thickness ensures easy manipulation and safe cable management:

3x cables (diameter up to 8 mm)

3x cables (diameter up to 5 mm)

CARIQ

panconnect•

CONNECTOR FIELD

CARIQ offers single connectors or their combinations in one field across all the panel sizes. Combinations of a grommet, sockets-only or sockets with USB-C/A charging are available as well. If you need atypical connector combination, contact our customer support.

2x LAN Cat6A (RJ45)

Cat6A S/FTP, to 500MHz, 10GBase-T, shielded housing, coupler

HDMI & LAN Cat6A (RJ45)

HDMI 2.0b, 4K 60 Hz, do 18Gbps, 150 mm
Cat6A S/FTP, to 500MHz, 10GBase-T, shielded housing, coupler

HDMI

HDMI 2.0b, 4K 60 Hz, to 18Gbps, 150 mm

USB-C & HDMI

USB-C 3.2 GEN 2, 10 Gbps, 150 mm
HDMI 2.0b, 4K 60 Hz, to 18Gbps, 150 mm

LAN Cat6A (RJ45)

Cat6A S/FTP, to 500MHz, 10GBase-T, shielded housing, coupler

USB-A & HDMI

USB-A 3.0 GEN 2, 5 Gbps, 150 mm
HDMI 2.0b, 4K 60 Hz, to 18Gbps, 150 mm

USB-C

USB-C 3.2 GEN 2, 10 Gbps, 150 mm

USB-C & LAN Cat6A (RJ45)

USB-C 3.2 GEN 2, 10 Gbps, 150 mm
Cat6A S/FTP, to 500MHz, 10GBase-T, shielded housing, coupler

USB-A

USB-A 3.0 GEN 2, 5 Gbps, 150 mm

USB-A & LAN Cat6A (RJ45)

USB-A 3.0 GEN 2, 5 Gbps, 150 mm
Cat6A S/FTP, to 500MHz, 10GBase-T, shielded housing, coupler

LIST OF VARIANTS

CARIQ XS, 2x SOCKET

BLACK	CAXS-2SC-B
WHITE	CAXS-2SC-W
SILVER	CAXS-2SC-S

CARIQ XS, 1x SOCKET, USB-C/A CHARGING

BLACK	CAXS-1SC-1AC-B
WHITE	CAXS-1SC-1AC-W
SILVER	CAXS-1SC-1AC-S

CARIQ XS, 1x SOCKET, GROMMET

BLACK	CAXS-1SC-1GR-B
WHITE	CAXS-1SC-1GR-W
SILVER	CAXS-1SC-1GR-S

CARIQ

panconnect•

CARIQ XS, 1x SOCKET, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails
in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F–F, 150 mm)

BLACK	CAXS-1SC-1H-B
WHITE	CAXS-1SC-1H-W
SILVER	CAXS-1SC-1H-S

RJ45 Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAXS-1SC-1L-B
WHITE	CAXS-1SC-1L-W
SILVER	CAXS-1SC-1L-S

USB-C 3.2 gen2 10 Gbps (F–F, 150 mm)

BLACK	CAXS-1SC-1C-B
WHITE	CAXS-1SC-1C-W
SILVER	CAXS-1SC-1C-S

USB-A 3.0, 5 Gbps, (F–F, 150 mm)

BLACK	CAXS-1SC-1A-B
WHITE	CAXS-1SC-1A-W
SILVER	CAXS-1SC-1A-S

2x Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAXS-1SC-2L-B
WHITE	CAXS-1SC-2L-W
SILVER	CAXS-1SC-2L-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAXS-1SC-1HL-B
WHITE	CAXS-1SC-1HL-W
SILVER	CAXS-1SC-1HL-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAXS-1SC-1HC-B
WHITE	CAXS-1SC-1HC-W
SILVER	CAXS-1SC-1HC-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAXS-1SC-1HA-B
WHITE	CAXS-1SC-1HA-W
SILVER	CAXS-1SC-1HA-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAXS-1SC-1CL-B
WHITE	CAXS-1SC-1CL-W
SILVER	CAXS-1SC-1CL-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAXS-1SC-1AL-B
WHITE	CAXS-1SC-1AL-W
SILVER	CAXS-1SC-1AL-S

CARIQ S, 3x SOCKET

BLACK	CAS-3SC-B
WHITE	CAS-3SC-W
SILVER	CAS-3SC-S

CARIQ S, 2x SOCKET, USB-C/A CHARGING

BLACK	CAS-2SC-1AC-B
WHITE	CAS-2SC-1AC-W
SILVER	CAS-2SC-1AC-S

CARIQ S, 2x SOCKET, GROMMET

BLACK	CAS-2SC-1GR-B
WHITE	CAS-2SC-1GR-W
SILVER	CAS-2SC-1GR-S

CARIQ S, 1x SOCKET, USB-C/A CHARGING, GROMMET

BLACK	CAS-1SC-1AC-1GR-B
WHITE	CAS-1SC-1AC-1GR-W
SILVER	CAS-1SC-1AC-1GR-S

BASICS   5   PRODUCT SHEET

CARIQ

panconnect•

CARIQ S, 2x SOCKET, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F–F, 150 mm)

BLACK	CAS-2SC-1H-B
WHITE	CAS-2SC-1H-W
SILVER	CAS-2SC-1H-S

RJ45 Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAS-2SC-1L-B
WHITE	CAS-2SC-1L-W
SILVER	CAS-2SC-1L-S

USB-C 3.2 gen2 10 Gbps (F–F, 150 mm)

BLACK	CAS-2SC-1C-B
WHITE	CAS-2SC-1C-W
SILVER	CAS-2SC-1C-S

USB-A 3.0, 5 Gbps, (F–F, 150 mm)

BLACK	CAS-2SC-1A-B
WHITE	CAS-2SC-1A-W
SILVER	CAS-2SC-1A-S

2x Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAS-2SC-2L-B
WHITE	CAS-2SC-2L-W
SILVER	CAS-2SC-2L-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAS-2SC-1HL-B
WHITE	CAS-2SC-1HL-W
SILVER	CAS-2SC-1HL-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAS-2SC-1HC-B
WHITE	CAS-2SC-1HC-W
SILVER	CAS-2SC-1HC-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAS-2SC-1HA-B
WHITE	CAS-2SC-1HA-W
SILVER	CAS-2SC-1HA-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAS-2SC-1CL-B
WHITE	CAS-2SC-1CL-W
SILVER	CAS-2SC-1CL-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAS-2SC-1AL-B
WHITE	CAS-2SC-1AL-W
SILVER	CAS-2SC-1AL-S

CARIQ S, 1x SOCKET, USB-C/A CHARGING, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F–F, 150 mm)

BLACK	CAS-1SC-1AC-1H-B
WHITE	CAS-1SC-1AC-1H-W
SILVER	CAS-1SC-1AC-1H-S

RJ45 Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAS-1SC-1AC-1L-B
WHITE	CAS-1SC-1AC-1L-W
SILVER	CAS-1SC-1AC-1L-S

USB-C 3.2 gen2 10 Gbps (F–F, 150 mm)

BLACK	CAS-1SC-1AC-1C-B
WHITE	CAS-1SC-1AC-1C-W
SILVER	CAS-1SC-1AC-1C-S

USB-A 3.0, 5 Gbps, (F–F, 150 mm)

BLACK	CAS-1SC-1AC-1A-B
WHITE	CAS-1SC-1AC-1A-W
SILVER	CAS-1SC-1AC-1A-S

2x Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAS-1SC-1AC-2L-B
WHITE	CAS-1SC-1AC-2L-W
SILVER	CAS-1SC-1AC-2L-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAS-1SC-1AC-1HL-B
WHITE	CAS-1SC-1AC-1HL-W
SILVER	CAS-1SC-1AC-1HL-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAS-1SC-1AC-1HC-B
WHITE	CAS-1SC-1AC-1HC-W
SILVER	CAS-1SC-1AC-1HC-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAS-1SC-1AC-1HA-B
WHITE	CAS-1SC-1AC-1HA-W
SILVER	CAS-1SC-1AC-1HA-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAS-1SC-1AC-1CL-B
WHITE	CAS-1SC-1AC-1CL-W
SILVER	CAS-1SC-1AC-1CL-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAS-1SC-1AC-1AL-B
WHITE	CAS-1SC-1AC-1AL-W
SILVER	CAS-1SC-1AC-1AL-S

CARIQ

panconnect●

CARIQ M, 4x SOCKET

BLACK	CAM-4SC-B
WHITE	CAM-4SC-W
SILVER	CAM-4SC-S

CARIQ M, 3x SOCKET, USB-C/A CHARGING

BLACK	CAM-3SC-1AC-B
WHITE	CAM-3SC-1AC-W
SILVER	CAM-3SC-1AC-S

CARIQ M, 3x SOCKET, GROMMET

BLACK	CAM-3SC-1GR-B
WHITE	CAM-3SC-1GR-W
SILVER	CAM-3SC-1GR-S

CARIQ M, 2x SOCKET, USB-C/A CHARGING, GROMMET

BLACK	CAM-2SC-1AC-1GR-B
WHITE	CAM-2SC-1AC-1GR-W
SILVER	CAM-2SC-1AC-1GR-S

CARIQ M, 3x SOCKET, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F-F, 150 mm)

BLACK	CAM-3SC-1H-B
WHITE	CAM-3SC-1H-W
SILVER	CAM-3SC-1H-S

RJ45 Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAM-3SC-1L-B
WHITE	CAM-3SC-1L-W
SILVER	CAM-3SC-1L-S

USB-C 3.2 gen2 10 Gbps (F-F, 150 mm)

BLACK	CAM-3SC-1C-B
WHITE	CAM-3SC-1C-W
SILVER	CAM-3SC-1C-S

USB-A 3.0, 5 Gbps, (F-F, 150 mm)

BLACK	CAM-3SC-1A-B
WHITE	CAM-3SC-1A-W
SILVER	CAM-3SC-1A-S

2x Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAM-3SC-2L-B
WHITE	CAM-3SC-2L-W
SILVER	CAM-3SC-2L-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAM-3SC-1HL-B
WHITE	CAM-3SC-1HL-W
SILVER	CAM-3SC-1HL-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAM-3SC-1HC-B
WHITE	CAM-3SC-1HC-W
SILVER	CAM-3SC-1HC-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAM-3SC-1HA-B
WHITE	CAM-3SC-1HA-W
SILVER	CAM-3SC-1HA-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAM-3SC-1CL-B
WHITE	CAM-3SC-1CL-W
SILVER	CAM-3SC-1CL-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAM-3SC-1AL-B
WHITE	CAM-3SC-1AL-W
SILVER	CAM-3SC-1AL-S

CARIQ

panconnect•

CARIQ M, 2x SOCKET, USB-C/A CHARGING, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F-F, 150 mm)

BLACK	CAM-2SC-1AC-1H-B
WHITE	CAM-2SC-1AC-1H-W
SILVER	CAM-2SC-1AC-1H-S

RJ45 Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAM-2SC-1AC-1L-B
WHITE	CAM-2SC-1AC-1L-W
SILVER	CAM-2SC-1AC-1L-S

USB-C 3.2 gen2 10 Gbps (F-F, 150 mm)

BLACK	CAM-2SC-1AC-1C-B
WHITE	CAM-2SC-1AC-1C-W
SILVER	CAM-2SC-1AC-1C-S

USB-A 3.0, 5 Gbps, (F-F, 150 mm)

BLACK	CAM-2SC-1AC-1A-B
WHITE	CAM-2SC-1AC-1A-W
SILVER	CAM-2SC-1AC-1A-S

2x Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAM-2SC-1AC-2L-B
WHITE	CAM-2SC-1AC-2L-W
SILVER	CAM-2SC-1AC-2L-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAM-2SC-1AC-1HL-B
WHITE	CAM-2SC-1AC-1HL-W
SILVER	CAM-2SC-1AC-1HL-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAM-2SC-1AC-1HC-B
WHITE	CAM-2SC-1AC-1HC-W
SILVER	CAM-2SC-1AC-1HC-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAM-2SC-1AC-1HA-B
WHITE	CAM-2SC-1AC-1HA-W
SILVER	CAM-2SC-1AC-1HA-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAM-2SC-1AC-1CL-B
WHITE	CAM-2SC-1AC-1CL-W
SILVER	CAM-2SC-1AC-1CL-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAM-2SC-1AC-1AL-B
WHITE	CAM-2SC-1AC-1AL-W
SILVER	CAM-2SC-1AC-1AL-S

CARIQ M, 2x SOCKET, GROMMET, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F-F, 150 mm)

BLACK	CAM-2SC-1H-1GR-B
WHITE	CAM-2SC-1H-1GR-W
SILVER	CAM-2SC-1H-1GR-S

RJ45 Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAM-2SC-1L-1GR-B
WHITE	CAM-2SC-1L-1GR-W
SILVER	CAM-2SC-1L-1GR-S

USB-C 3.2 gen2 10 Gbps (F-F, 150 mm)

BLACK	CAM-2SC-1C-1GR-B
WHITE	CAM-2SC-1C-1GR-W
SILVER	CAM-2SC-1C-1GR-S

USB-A 3.0, 5 Gbps, (F-F, 150 mm)

BLACK	CAM-2SC-1A-1GR-B
WHITE	CAM-2SC-1A-1GR-W
SILVER	CAM-2SC-1A-1GR-S

2x Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAM-2SC-2L-1GR-B
WHITE	CAM-2SC-2L-1GR-W
SILVER	CAM-2SC-2L-1GR-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAM-2SC-1HL-1GR-B
WHITE	CAM-2SC-1HL-1GR-W
SILVER	CAM-2SC-1HL-1GR-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAM-2SC-1HC-1GR-B
WHITE	CAM-2SC-1HC-1GR-W
SILVER	CAM-2SC-1HC-1GR-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAM-2SC-1HA-1GR-B
WHITE	CAM-2SC-1HA-1GR-W
SILVER	CAM-2SC-1HA-1GR-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAM-2SC-1CL-1GR-B
WHITE	CAM-2SC-1CL-1GR-W
SILVER	CAM-2SC-1CL-1GR-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAM-2SC-1AL-1GR-B
WHITE	CAM-2SC-1AL-1GR-W
SILVER	CAM-2SC-1AL-1GR-S

CARIQ

panconnect•

CARIQ M, 1x SOCKET, USB-C/A CHARGING, GROMMET, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F-F, 150 mm)

BLACK	CAM-1SC-1AC-1H-1GR-B
WHITE	CAM-1SC-1AC-1H-1GR-W
SILVER	CAM-1SC-1AC-1H-1GR-S

RJ45 Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAM-1SC-1AC-1L-1GR-B
WHITE	CAM-1SC-1AC-1L-1GR-W
SILVER	CAM-1SC-1AC-1L-1GR-S

USB-C 3.2 gen2 10 Gbps (F-F, 150 mm)

BLACK	CAM-1SC-1AC-1C-1GR-B
WHITE	CAM-1SC-1AC-1C-1GR-W
SILVER	CAM-1SC-1AC-1C-1GR-S

USB-A 3.0, 5 Gbps, (F-F, 150 mm)

BLACK	CAM-1SC-1AC-1A-1GR-B
WHITE	CAM-1SC-1AC-1A-1GR-W
SILVER	CAM-1SC-1AC-1A-1GR-S

2x Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAM-1SC-1AC-2L-1GR-B
WHITE	CAM-1SC-1AC-2L-1GR-W
SILVER	CAM-1SC-1AC-2L-1GR-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAM-1SC-1AC-1HL-1GR-B
WHITE	CAM-1SC-1AC-1HL-1GR-W
SILVER	CAM-1SC-1AC-1HL-1GR-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAM-1SC-1AC-1HC-1GR-B
WHITE	CAM-1SC-1AC-1HC-1GR-W
SILVER	CAM-1SC-1AC-1HC-1GR-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAM-1SC-1AC-1HA-1GR-B
WHITE	CAM-1SC-1AC-1HA-1GR-W
SILVER	CAM-1SC-1AC-1HA-1GR-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAM-1SC-1AC-1CL-1GR-B
WHITE	CAM-1SC-1AC-1CL-1GR-W
SILVER	CAM-1SC-1AC-1CL-1GR-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAM-1SC-1AC-1AL-1GR-B
WHITE	CAM-1SC-1AC-1AL-1GR-W
SILVER	CAM-1SC-1AC-1AL-1GR-S

CARIQ L, 5x SOCKET

BLACK	CAL-5SC-B
WHITE	CAL-5SC-W
SILVER	CAL-5SC-S

CARIQ L, 4x SOCKET, USB-C/A CHARGING

BLACK	CAL-4SC-1AC-B
WHITE	CAL-4SC-1AC-W
SILVER	CAL-4SC-1AC-S

CARIQ L, 4x SOCKET, GROMMET

BLACK	CAL-4SC-1GR-B
WHITE	CAL-4SC-1GR-W
SILVER	CAL-4SC-1GR-S

CARIQ L, 3x SOCKET, USB-C/A CHARGING, GROMMET

BLACK	CAL-3SC-1AC-1GR-B
WHITE	CAL-3SC-1AC-1GR-W
SILVER	CAL-3SC-1AC-1GR-S

CARIQ L, 2x SOCKET, 2x USB-C/A GROMMET

BLACK	CAL-2SC-2AC-B
WHITE	CAL-2SC-2AC-W
SILVER	CAL-2SC-2AC-S

CARIQ

panconnect•

CARIQ L, 4x SOCKET, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F-F, 150 mm)

BLACK	CAL-4SC-1H-B
WHITE	CAL-4SC-1H-W
SILVER	CAL-4SC-1H-S

RJ45 Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAL-4SC-1L-B
WHITE	CAL-4SC-1L-W
SILVER	CAL-4SC-1L-S

USB-C 3.2 gen2 10 Gbps (F-F, 150 mm)

BLACK	CAL-4SC-1C-B
WHITE	CAL-4SC-1C-W
SILVER	CAL-4SC-1C-S

USB-A 3.0, 5 Gbps, (F-F, 150 mm)

BLACK	CAL-4SC-1A-B
WHITE	CAL-4SC-1A-W
SILVER	CAL-4SC-1A-S

2x Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAL-4SC-2L-B
WHITE	CAL-4SC-2L-W
SILVER	CAL-4SC-2L-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAL-4SC-1HL-B
WHITE	CAL-4SC-1HL-W
SILVER	CAL-4SC-1HL-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAL-4SC-1HC-B
WHITE	CAL-4SC-1HC-W
SILVER	CAL-4SC-1HC-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAL-4SC-1HA-B
WHITE	CAL-4SC-1HA-W
SILVER	CAL-4SC-1HA-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAL-4SC-1CL-B
WHITE	CAL-4SC-1CL-W
SILVER	CAL-4SC-1CL-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAL-4SC-1AL-B
WHITE	CAL-4SC-1AL-W
SILVER	CAL-4SC-1AL-S

CARIQ L, 3x SOCKET, USB-C/A CHARGING, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F-F, 150 mm)

BLACK	CAL-3SC-1AC-1H-B
WHITE	CAL-3SC-1AC-1H-W
SILVER	CAL-3SC-1AC-1H-S

RJ45 Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAL-3SC-1AC-1L-B
WHITE	CAL-3SC-1AC-1L-W
SILVER	CAL-3SC-1AC-1L-S

USB-C 3.2 gen2 10 Gbps (F-F, 150 mm)

BLACK	CAL-3SC-1AC-1C-B
WHITE	CAL-3SC-1AC-1C-W
SILVER	CAL-3SC-1AC-1C-S

USB-A 3.0, 5 Gbps, (F-F, 150 mm)

BLACK	CAL-3SC-1AC-1A-B
WHITE	CAL-3SC-1AC-1A-W
SILVER	CAL-3SC-1AC-1A-S

2x Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAL-3SC-1AC-2L-B
WHITE	CAL-3SC-1AC-2L-W
SILVER	CAL-3SC-1AC-2L-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAL-3SC-1AC-1HL-B
WHITE	CAL-3SC-1AC-1HL-W
SILVER	CAL-3SC-1AC-1HL-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAL-3SC-1AC-1HC-B
WHITE	CAL-3SC-1AC-1HC-W
SILVER	CAL-3SC-1AC-1HC-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAL-3SC-1AC-1HA-B
WHITE	CAL-3SC-1AC-1HA-W
SILVER	CAL-3SC-1AC-1HA-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAL-3SC-1AC-1CL-B
WHITE	CAL-3SC-1AC-1CL-W
SILVER	CAL-3SC-1AC-1CL-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAL-3SC-1AC-1AL-B
WHITE	CAL-3SC-1AC-1AL-W
SILVER	CAL-3SC-1AC-1AL-S

CARIQ

panconnect•

CARIQ L, 3x SOCKET, GROMMET, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F–F, 150 mm)

BLACK	CAL-3SC-1H-1GR-B
WHITE	CAL-3SC-1H-1GR-W
SILVER	CAL-3SC-1H-1GR-S

RJ45 Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAL-3SC-1L-1GR-B
WHITE	CAL-3SC-1L-1GR-W
SILVER	CAL-3SC-1L-1GR-S

USB-C 3.2 gen2 10 Gbps (F–F, 150 mm)

BLACK	CAL-3SC-1C-1GR-B
WHITE	CAL-3SC-1C-1GR-W
SILVER	CAL-3SC-1C-1GR-S

USB-A 3.0, 5 Gbps, (F–F, 150 mm)

BLACK	CAL-3SC-1A-1GR-W
WHITE	CAL-3SC-1A-1GR-W
SILVER	CAL-3SC-1A-1GR-S

2x Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAL-3SC-2L-1GR-B
WHITE	CAL-3SC-2L-1GR-W
SILVER	CAL-3SC-2L-1GR-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAL-3SC-1HL-1GR-B
WHITE	CAL-3SC-1HL-1GR-W
SILVER	CAL-3SC-1HL-1GR-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAL-3SC-1HC-1GR-B
WHITE	CAL-3SC-1HC-1GR-W
SILVER	CAL-3SC-1HC-1GR-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAL-3SC-1HA-1GR-B
WHITE	CAL-3SC-1HA-1GR-W
SILVER	CAL-3SC-1HA-1GR-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAL-3SC-1CL-1GR-B
WHITE	CAL-3SC-1CL-1GR-W
SILVER	CAL-3SC-1CL-1GR-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAL-3SC-1AL-1GR-B
WHITE	CAL-3SC-1AL-1GR-W
SILVER	CAL-3SC-1AL-1GR-S

CARIQ L, 2x SOCKET, USB-C/A CHARGING, GROMMET, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F–F, 150 mm)

BLACK	CAL-2SC-1AC-1H-1GR-B
WHITE	CAL-2SC-1AC-1H-1GR-W
SILVER	CAL-2SC-1AC-1H-1GR-S

RJ45 Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAL-2SC-1AC-1L-1GR-B
WHITE	CAL-2SC-1AC-1L-1GR-W
SILVER	CAL-2SC-1AC-1L-1GR-S

USB-C 3.2 gen2 10 Gbps (F–F, 150 mm)

BLACK	CAL-2SC-1AC-1C-1GR-B
WHITE	CAL-2SC-1AC-1C-1GR-W
SILVER	CAL-2SC-1AC-1C-1GR-S

USB-A 3.0, 5 Gbps, (F–F, 150 mm)

BLACK	CAL-2SC-1AC-1A-1GR-B
WHITE	CAL-2SC-1AC-1A-1GR-W
SILVER	CAL-2SC-1AC-1A-1GR-S

2x Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAL-2SC-1AC-2L-1GR-B
WHITE	CAL-2SC-1AC-2L-1GR-W
SILVER	CAL-2SC-1AC-2L-1GR-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAL-2SC-1AC-1HL-1GR-B
WHITE	CAL-2SC-1AC-1HL-1GR-W
SILVER	CAL-2SC-1AC-1HL-1GR-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAL-2SC-1AC-1HC-1GR-B
WHITE	CAL-2SC-1AC-1HC-1GR-W
SILVER	CAL-2SC-1AC-1HC-1GR-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAL-2SC-1AC-1HA-1GR-B
WHITE	CAL-2SC-1AC-1HA-1GR-W
SILVER	CAL-2SC-1AC-1HA-1GR-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAL-2SC-1AC-1CL-1GR-B
WHITE	CAL-2SC-1AC-1CL-1GR-W
SILVER	CAL-2SC-1AC-1CL-1GR-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAL-2SC-1AC-1AL-1GR-B
WHITE	CAL-2SC-1AC-1AL-1GR-W
SILVER	CAL-2SC-1AC-1AL-1GR-S

CARIQ

panconnect•

CARIQ XL, 6x SOCKET

BLACK	CAXL-6SC-B
WHITE	CAXL-6SC-W
SILVER	CAXL-6SC-S

CARIQ XL, 5x SOCKET, USB-C/A CHARGING

BLACK	CAXL-5SC-1AC-B
WHITE	CAXL-5SC-1AC-W
SILVER	CAXL-5SC-1AC-S

CARIQ XL, 5x SOCKET, GROMMET

BLACK	CAXL-5SC-1GR-B
WHITE	CAXL-5SC-1GR-W
SILVER	CAXL-5SC-1GR-S

CARIQ XL, 4x SOCKET, USB-C/A CHARGING, GROMMET

BLACK	CAXL-4SC-1AC-1GR-B
WHITE	CAXL-4SC-1AC-1GR-W
SILVER	CAXL-4SC-1AC-1GR-S

CARIQ XL, 5x SOCKET, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F-F, 150 mm)

BLACK	CAXL-5SC-1H-B
WHITE	CAXL-5SC-1H-W
SILVER	CAXL-5SC-1H-S

RJ45 Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAXL-5SC-1L-B
WHITE	CAXL-5SC-1L-W
SILVER	CAXL-5SC-1L-S

USB-C 3.2 gen2 10 Gbps (F-F, 150 mm)

BLACK	CAXL-5SC-1C-B
WHITE	CAXL-5SC-1C-W
SILVER	CAXL-5SC-1C-S

USB-A 3.0, 5 Gbps, (F-F, 150 mm)

BLACK	CAXL-5SC-1A-B
WHITE	CAXL-5SC-1A-W
SILVER	CAXL-5SC-1A-S

2x Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAXL-5SC-2L-B
WHITE	CAXL-5SC-2L-W
SILVER	CAXL-5SC-2L-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAXL-5SC-1HL-B
WHITE	CAXL-5SC-1HL-W
SILVER	CAXL-5SC-1HL-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAXL-5SC-1HC-B
WHITE	CAXL-5SC-1HC-W
SILVER	CAXL-5SC-1HC-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAXL-5SC-1HA-B
WHITE	CAXL-5SC-1HA-W
SILVER	CAXL-5SC-1HA-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAXL-5SC-1CL-B
WHITE	CAXL-5SC-1CL-W
SILVER	CAXL-5SC-1CL-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAXL-5SC-1AL-B
WHITE	CAXL-5SC-1AL-W
SILVER	CAXL-5SC-1AL-S

CARIQ

CARIQ XL, 4x SOCKET, USB-C/A CHARGING, CONNECOTR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails
in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F–F, 150 mm)

BLACK	CAXL-4SC-1AC-1H-B
WHITE	CAXL-4SC-1AC-1H-W
SILVER	CAXL-4SC-1AC-1H-S

RJ45 Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAXL-4SC-1AC-1L-B
WHITE	CAXL-4SC-1AC-1L-W
SILVER	CAXL-4SC-1AC-1L-S

USB-C 3.2 gen2 10 Gbps (F–F, 150 mm)

BLACK	CAXL-4SC-1AC-1C-B
WHITE	CAXL-4SC-1AC-1C-W
SILVER	CAXL-4SC-1AC-1C-S

USB-A 3.0, 5 Gbps, (F–F, 150 mm)

BLACK	CAXL-4SC-1AC-1A-B
WHITE	CAXL-4SC-1AC-1A-W
SILVER	CAXL-4SC-1AC-1A-S

2x Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAXL-4SC-1AC-2L-B
WHITE	CAXL-4SC-1AC-2L-W
SILVER	CAXL-4SC-1AC-2L-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAXL-4SC-1AC-1HL-B
WHITE	CAXL-4SC-1AC-1HL-W
SILVER	CAXL-4SC-1AC-1HL-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAXL-4SC-1AC-1HC-B
WHITE	CAXL-4SC-1AC-1HC-W
SILVER	CAXL-4SC-1AC-1HC-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAXL-4SC-1AC-1HA-B
WHITE	CAXL-4SC-1AC-1HA-W
SILVER	CAXL-4SC-1AC-1HA-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAXL-4SC-1AC-1CL-B
WHITE	CAXL-4SC-1AC-1CL-W
SILVER	CAXL-4SC-1AC-1CL-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAXL-4SC-1AC-1AL-B
WHITE	CAXL-4SC-1AC-1AL-W
SILVER	CAXL-4SC-1AC-1AL-S

CARIQ XL, 4x SOCKET, GROMMET, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails
in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F–F, 150 mm)

BLACK	CAXL-4SC-1H-1GR-B
WHITE	CAXL-4SC-1H-1GR-W
SILVER	CAXL-4SC-1H-1GR-S

RJ45 Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAXL-4SC-1L-1GR-B
WHITE	CAXL-4SC-1L-1GR-W
SILVER	CAXL-4SC-1L-1GR-S

USB-C 3.2 gen2 10 Gbps (F–F, 150 mm)

BLACK	CAXL-4SC-1C-1GR-B
WHITE	CAXL-4SC-1C-1GR-W
SILVER	CAXL-4SC-1C-1GR-S

USB-A 3.0, 5 Gbps, (F–F, 150 mm)

BLACK	CAXL-4SC-1A-1GR-B
WHITE	CAXL-4SC-1A-1GR-W
SILVER	CAXL-4SC-1A-1GR-S

2x Cat6A S/FTP, 10GBase-T (F–F, coupler)

BLACK	CAXL-4SC-2L-1GR-B
WHITE	CAXL-4SC-2L-1GR-W
SILVER	CAXL-4SC-2L-1GR-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAXL-4SC-1HL-1GR-B
WHITE	CAXL-4SC-1HL-1GR-W
SILVER	CAXL-4SC-1HL-1GR-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAXL-4SC-1HC-1GR-B
WHITE	CAXL-4SC-1HC-1GR-W
SILVER	CAXL-4SC-1HC-1GR-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAXL-4SC-1HA-1GR-B
WHITE	CAXL-4SC-1HA-1GR-W
SILVER	CAXL-4SC-1HA-1GR-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAXL-4SC-1CL-1GR-B
WHITE	CAXL-4SC-1CL-1GR-W
SILVER	CAXL-4SC-1CL-1GR-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAXL-4SC-1AL-1GR-B
WHITE	CAXL-4SC-1AL-1GR-W
SILVER	CAXL-4SC-1AL-1GR-S

CARIQ

panconnect.

CARIQ XL, 3x SOCKET, USB-C/A CHARGING, GROMMET, CONNECTOR FIELD

Connector field contains one or two connectors - see below. They are equipped with pigtails in the indicated length and lead out of the panel.

HDMI 2.0b 4K 60Hz, (F-F, 150 mm)

BLACK	CAXL-3SC-1AC-1H-1GR-B
WHITE	CAXL-3SC-1AC-1H-1GR-W
SILVER	CAXL-3SC-1AC-1H-1GR-S

RJ45 Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAXL-3SC-1AC-1L-1GR-B
WHITE	CAXL-3SC-1AC-1L-1GR-W
SILVER	CAXL-3SC-1AC-1L-1GR-S

USB-C 3.2 gen2 10 Gbps (F-F, 150 mm)

BLACK	CAXL-3SC-1AC-1C-1GR-B
WHITE	CAXL-3SC-1AC-1C-1GR-W
SILVER	CAXL-3SC-1AC-1C-1GR-S

USB-A 3.0, 5 Gbps, (F-F, 150 mm)

BLACK	CAXL-3SC-1AC-1A-1GR-B
WHITE	CAXL-3SC-1AC-1A-1GR-W
SILVER	CAXL-3SC-1AC-1A-1GR-S

2x Cat6A S/FTP, 10GBase-T (F-F, coupler)

BLACK	CAXL-3SC-1AC-2L-1GR-B
WHITE	CAXL-3SC-1AC-2L-1GR-W
SILVER	CAXL-3SC-1AC-2L-1GR-S

RJ45 Cat6A S/FTP + HDMI 4K 60Hz

BLACK	CAXL-3SC-1AC-1HL-1GR-B
WHITE	CAXL-3SC-1AC-1HL-1GR-W
SILVER	CAXL-3SC-1AC-1HL-1GR-S

USB-C 3.2 gen2 + HDMI 4K 60Hz

BLACK	CAXL-3SC-1AC-1HC-1GR-B
WHITE	CAXL-3SC-1AC-1HC-1GR-W
SILVER	CAXL-3SC-1AC-1HC-1GR-S

USB-A 3.0 + HDMI 4K 60Hz

BLACK	CAXL-3SC-1AC-1HA-1GR-B
WHITE	CAXL-3SC-1AC-1HA-1GR-W
SILVER	CAXL-3SC-1AC-1HA-1GR-S

RJ45 Cat6A S/FTP + USB-C 3.2 gen2

BLACK	CAXL-3SC-1AC-1CL-1GR-B
WHITE	CAXL-3SC-1AC-1CL-1GR-W
SILVER	CAXL-3SC-1AC-1CL-1GR-S

RJ45 Cat6A S/FTP + USB-A 3.0

BLACK	CAXL-3SC-1AC-1AL-1GR-B
WHITE	CAXL-3SC-1AC-1AL-1GR-W
SILVER	CAXL-3SC-1AC-1AL-1GR-S

CARIQ

panconnect•

INSTALLATION INSTRUCTION

CARIQ is installed in the same way for all sizes, just with different cut lengths.

In order to install CARIQ, you will require a jig saw and a round drill with a diameter of 68mm (Ø68mm). It is worth noting that the installation process is also compatible with CNC milling.

1 | Mark the two outermost holes and use a round drill to drill them.

2 | Connect the openings using a jig saw, creating a hole shaped as pictured

3 | Insert the panel into the opening, place the mounting frame underneath, and tighten the screws according to the strength of the tabletop.

4 | Connect the panel to the electrical socket and AV connection (if equipped).

PRODUCT PACKAGE

CARIQ panel with power cable, mounting frame, and a set of screws for attaching the mounting frame.

THICKNESS OF THE DESK

10 - 40 mm (possibility up to 60 mm with custom screws , not part of a standard package)

INSTALLATION MANUAL

panconnect.eu/en/download/

SAFETY & RECYCLATION

(CE)

PANCONNECT declares that panel CARIQ complies with Low voltage directive 2014/35/EU and EMC directive 2014/30/EU. Testing has been made according to EN 50491-5-1:2010 and EN 50491-5-2:2010 standards.

All products from PANCONNECT are intended for upgrade or recyclation in accordance with the company's policy. Before the disposal of this panel comes up, please verify if this product can or cannot be upgraded or overhauled. If it's not possible, kindly arrange the disposal in accordance with valid EU directives.

This product belongs to WASTE ELECTRICAL AND ELECTRONIC EQUIPMENT (WEEE) category so the disposal is possible only in accordance with this WEEE Directive 2012/19/EU.
It cannot be part of the municipal waste. For more information please check www.asekol.cz | info@asekol.cz

ABOUT THE MANUFACTURER

panconnect•

PANCONNECT s.r.o.
Olomoucká 601/51, 618 00 Brno
Pobřežní 249/46, 186 00 Praha
ID: 29265703, VAT ID: CZ29265703

sales@panconnect.eu, +420 603 575 486
support@panconnect.eu, +420 731 145 272
web: www.panconnect.eu
portal and configurator: pro.panconnect.eu